



**General Description:**

MM-MPA-092096-20-28 is a Waveguide Power Amplifier that operates over the frequency range of 92 to 96 GHz. This model provides a typical gain of 20 dB . It provides a Psat of 28 dB typical and operates on +16 VDC with a typical current draw of 600 mA.

**Features:**

- Ultra Wide Band: 90-96 GHz
- Gain: 20 dB
- Psat: 28 dB
- Internally regulated
- Unconditionally stable

**Applications:**

- Radar Systems
- Communication Systems
- Receivers Systems

**Electrical Specifications (23° C):**

| Parameter           | Value |     |     | Units |
|---------------------|-------|-----|-----|-------|
|                     | Min   | Typ | Max |       |
| Frequency Range     | 92    |     | 96  | GHz   |
| Gain                | 20    | 22  |     | dB    |
| Gain Flatness       |       | -   |     | dB    |
| Psat                | 28    | 29  |     | dBm   |
| Output Power (P1dB) |       | -   |     | dBm   |
| Input VSWR          |       | 2.0 |     | :1    |
| Output VSWR         |       | 2.0 |     | :1    |
| DC Voltage          |       | +16 |     | V     |
| DC Current          |       | 600 |     | mA    |

**Absolute Maximum Ratings:**

| Condition               | Value                |
|-------------------------|----------------------|
| DC Voltage              | +16 V                |
| Maximum Input Power(CW) | TBD                  |
| ESD sensitivity (HBm)   | Class 0, passed 150V |

**Mechanical Specifications:**

| Parameter    | Value       |
|--------------|-------------|
| Length       | 87 mm       |
| Width        | 68 mm       |
| Height       | 54 mm       |
| RF Connector | WR10/UG-387 |



Mountain Microwave


Focus on the future

Waveguide Power Amplifier

MM-MPA-092096-20-28

92 to 96 GHz

Outline Drawing:



mm(Inches)

Environmental Conditions:

| Parameter               | Standard                            | Description                   |
|-------------------------|-------------------------------------|-------------------------------|
| Operational Temperature |                                     | -10°C~+40°C                   |
| Storage Temperature     |                                     | -45°C~+125°C                  |
| Random Vibration        | MIL-STD-883K, Method 2026, Cond. IB | 50 - 2000 Hz, 7.3 Grms        |
| Humidity                | MIL-STD-202, Method 103B, Cond. B   | 100% RH at 35c, 95%RH at 40°C |
| Altitude                | MIL-STD-883K, Method 1001, Cond. C  | 50,000 feet                   |

Caution:

- Exceeding absolute maximum ratings shown will damage the device.
- The device is static sensitive. Always follow ESD rules when working with the device.
- Heat Sink required during operation.

Please note, all information contained in this data sheet is subject to change without notice.

ver 2.0 0318